

Intake / Exhaust Grilles



duct grille w/ metal collar for joist mount 4", 6", 8" available



duct grille w/ locking ring for ceiling mount 4", 6", 8" available



Return/exhaust grille assembly w/adjustable damper; fits 4", 6", 8" duct* * Rough-in flanges available; inquire



Grille/light; 7" ceiling mount w/14 watt fluorescent bulb; 4" duct; Energy Star

Roof Vent Caps



Milled aluminum 4", up to 7", up to 10"

Self-Dampening Vent Hoods



louvered white plastic with tailpiece 4", 6" available



wide mouthed aluminum with tailpiece 4", 6", 3 1/4" x 10" available

Backdraft Dampers



Inline metal 4", 6", 8" available

Duct Connectors



metal Y 4", 6", 8" available



metal T 4", 6" available



metal straight 4", 6" available

Undampered Intake/ Exhaust Vent w/Screen



4" white plastic wide mouth with tailpiece



6" louvered white plastic

Makeup Air Inlets



AIRLET 200, 5" x 9", 5 1/8" round sleeve, white grille

Reducers / Clamps



5" x 4" metal reducer 6" x 4" metal reducer 6" x 5" metal reducer



Metal worm drive 4", 6", 8" available

Duct



Flexible Vinyl 4" x 8' 4" x 20' 4" x 50'



Foil-Laminate Flex
- UL Listed
4" x 25'
6" x 25'
8" x 25'



Semi-Rigid Aluminum 4" x 8' 4" x 25' 6" x 8' 6" x 25'



Insulated Flexible - UL Listed 4" x 25' 6" x 25' 8" x 25'

Fan Controls



Fan speed control (Motor Rated)



Humidity-activated switch (adjusts from 20-80% RH)

Marktime



For Greener building and energy savings, install a MarkTime® switch with a Spruce Energy Star® fan. Control energy use as well as mold and mildew in high moisture environments with a MARKTIME® switch. MARKTIME® switches can be used in many applications in combination with exhaust fans, lights, and heat lamps.

MarkTime Switches



MarkTime® fan/light timer switch, ivory; 2 position, on/time-delay off

MarkTime® fan/light timer switch, white; 2 position, on/time-delay off



MarkTime® digital fan/light timer switch, white/ivory decorative overlay; time-delay off at 20, 40 or 60 min.



MarkTime® digital timer switch, white/ivory decorative overlay; time-delay off at 15, 30, 60 or 120 min.





www.spruce.com sales@spruce.com

800-355-0901 Fax: 978-521-3964

Spruce Environmental Technologies, Inc. 3 Saber Way Ward Hill, MA 01835

