



# OPPOSED BLADE DAMPER (OBV) SPECIFICATION SHEET

	<b>ACCESSORIES</b> OPPOSED BLADE DAMPER <b>MODELS: OB, OB-L, OB-FL</b>		
	<b>SUSTAINABLE EXTRUDED ALUMINUM</b>		

Dimensions are in inches

	<p><b>OB</b></p> <p>Opposed blade damper .</p>
	<p><b>OB-L</b></p> <p>Opposed blade damper with legs.</p>
	<p><b>OB-FL</b></p> <p>Opposed blade damper with fire link.</p>

<p><b>DESCRIPTION:</b></p> <ol style="list-style-type: none"> <li>The model OB is 6063 extruded aluminum alloy construction and utilizes nylon bushings where the blades meet the frame to eliminate corrosion and vibration. The unit is used in conjunction with all products. it is screwdriver-operated and allows for precise balancing with minimum leakage.</li> <li>The model OB-L is identical to OB with the exception that the unit has four or more legs for duct mounting.</li> <li>The model OB-FL is identical to OB with the exception that a UL-approved fire links is mounted to the frame of the unit that automatically springs the blades closed without having any interference by the fire link assembly.</li> </ol>			
<p><b>PROJECT:</b></p>			

<p><b>ENGINEER:</b></p>	<p><b>DATE</b></p>	<p><b>SERIES</b></p>	<p><b>DRAWING NO.</b></p>
<p><b>CONTRACTOR:</b></p>			

AirGuide Manufacturing, LLC. reserves the right to change any information concerning product or pricing without notice.



#2 Chootoo Road, South Aranguez, San Juan, Trinidad

